



THE UNIVERSITY *of* EDINBURGH

Edinburgh Research Explorer

## Effect of vapor pressure on the performance of a Leidenfrost engine

### Citation for published version:

Agrawal, P, Wells, GG, Ledesma-Aguilar, R, McHale, G, Buchoux, A, Sefiane, K, Stokes, A, Walton, A & Terry, J 2019, 'Effect of vapor pressure on the performance of a Leidenfrost engine', 72nd Annual Meeting of the APS Division of Fluid Dynamics , Seattle, United States, 23/11/19 - 26/11/19.

### Link:

[Link to publication record in Edinburgh Research Explorer](#)

### Document Version:

Publisher's PDF, also known as Version of record

### General rights

Copyright for the publications made accessible via the Edinburgh Research Explorer is retained by the author(s) and / or other copyright owners and it is a condition of accessing these publications that users recognise and abide by the legal requirements associated with these rights.

### Take down policy

The University of Edinburgh has made every reasonable effort to ensure that Edinburgh Research Explorer content complies with UK legislation. If you believe that the public display of this file breaches copyright please contact [openaccess@ed.ac.uk](mailto:openaccess@ed.ac.uk) providing details, and we will remove access to the work immediately and investigate your claim.



Abstract Submitted  
for the DFD19 Meeting of  
The American Physical Society

**Effect of vapor pressure on the performance of a Leidenfrost engine** PRASHANT AGRAWAL, GARY WELLS, RODRIGO LEDESMA-AGUILAR, GLEN MCHALE, Northumbria University, ANTHONY BUCHOUX, KHELLIL SEFIANE, ADAM STOKES, ANTHONY WALTON, JONATHAN TERRY, The University of Edinburgh — Friction is a hindrance to effective mechanical energy conversion, especially at microscales where significant wear occurs due to a high surface-area to volume ratio. Recently, we have developed the concept of a virtually frictionless heat engine, employing levitating liquids (or solids) on turbine-inspired substrates to convert thermal energy to mechanical motion. The levitation is achieved via the Leidenfrost effect, where a liquid drop levitates on its own vapor when it contacts a substrate heated to temperatures significantly above the liquid's boiling point. The vapor layer virtually eliminates friction and allows evaporating drops to self-propel on asymmetrically textured substrates. In this work, we operate this Leidenfrost heat engine continuously and control its output power by mechanically altering the vapor layer thickness. This is done by replenishing the liquid and supporting the rotor using a bearing assembly. We observe an increase in the power output despite the added bearing friction. The design principles described here can be extrapolated to develop mm and sub-mm scale engines for applications in extreme environments with naturally occurring low pressures and high temperature differences. We acknowledge funding from UK EPSRC (EP/P005896/1 and EP/P005705/1)

Prashant Agrawal  
Northumbria University

Date submitted: 31 Jul 2019

Electronic form version 1.4